Photovoltaic – Trainingsystem for vocational and advanced training

The Solar branch is one of the important growth market of the furture. The number of jobs grows, the demand of specialists and executive staffs increases continuous. For this reason worldwide the vocational and advanced training in the field of photovoliiac will become more and more important.



Development

In cooperation with the ISET - Institut für Solare Energieversorgungstechnik e. V. (now: Frauenhofer Institut für Windenergie und Energiesystemtechnik IWES) in Kassel the company IKS Photovoltaik developed the Photovoltaic-Trainingsystem Solartrainer profi.

Application

The PV-Trainingsystem is suited for the instruction at schools, vocational training Schools, training centres, evening classes and universities. Supported learning objectives can be electrical and system engineering , construction, mode of operation, connecting and installation of PV-plants. It can be used both to the supplementary demonstration of lessons and courses as well as for the use in practical training.

Construction

The system consists of individual plugin units each with components for different experimental arrangements. The plugin units are put in the rackside and connected according to the demand. The conception of the system allows indoor and outdoor experiments

Indoor experiments are easily possible among others because of the system included PV-module

plus module stand. Using a dimmable spotlight which is vertically as well as horizontally movable fixed to an outrigger, seasonal daily curves can easily be simulated.

Additional options are the change of slope angle and the simulation of the influence of irradiation and temperature on the characteristic curve of a PVmodule.

To ensure a reproducibility of measurements and not to depend on the weather, a PV-module simulator was developed, which exactly simulates the behaviour of a PV-module. The short circuit current can be adjusted.



What a pupil or trainee can work out on his own in practice oriented labscale experiments, is transferable to real systems without problems.

SOLARTRAINER





Flexible

The modular conception of the system allows the selection of the plug-in units and components for the different training objectives.

The at any time possible enlargement and integration of new technology assure a system that is always state of-the-art.

Instructional materials

An experimental instruction as well as two developed training sessions are available. German English Spanish French

Experiments

The basic principles of photovoltaics considering the influence of different parameters can also be imparted as the application of direct connected small systems, the mains behaviour of stand alone systems and the especially for craftsmen very important line powered operation mode:

- Characteristic curve of a diode, respectively a diode series
- Characteristic curve of a solar module (I/U) and (U/P), MPP
- Characteristic curve of a solar module (I/U) depending on irradiation
- Characteristic curve of a solar module (I/U) depending on temperature
- Power output of a solar module depending On the angle of incidence of the light
- Simulation: Power output of a solar module depending on the position of the sun (morning to evening / winter- and summertime)
- Series connection of solar modules
- Parallel connection of solar modules
- Series connection of solar modules and shadowing without bypass-diode
- Series connection of solar modules and shadowing with bypass-diode
- Grid parallel operation mode
 Different operation modes and directions of electric energy power flow. Calculation of the efficiency (inverter)
- Stand alone systems DC and AC. Different operation modes
- Integration of outdoor solar module



The listing does not contain all experiments which are possible to carry out. The possibility of carrying out the experiments is depending on the equipment. Technical changes reserved 2014-06

SOLARTRAINER







ST 01 Solar Module Connection Indoor

For connecting the solar module of "ST 14 module stand" to the socket on the front. The two front sockets of the schematically shown solar module can be connected to a variable load (e.g. ST 20 B). Measuring of voltage and current.



ST 05 O / ST 05 D Inverter Grid Connection

Transforms direct current into sinusoidal alternating current, single-phase feed-in, line-commutated. Input 28 - 50 V DC, MPP-tracking AC power approx. 110 W Available versions: 230 V / 50 Hz (ST 05 O /ST 05 D) 230 V / 60 Hz (ST 05 D) 115 V / 60 Hz (ST 05 D)



ST 02 Solar Module Simulated

Solar module simulator for the exact simulation of a solar module.

Short circuit current can be adjusted in steps or variably. Parallel and series connection possible

Switchable bypass diode. Mains connection 230 V / 50-60

Open circuit voltage 23.1 V, short circuit current 0 -1.5 A, rated power 24 Wp



ST 06 R Inverter Island Grid

Transforms direct current into rectangular alternating current for operation of an island grid system. Input 12 V DC/8 A, output 230 V / 50 Hz. AC power approx. 100 W



ST 03 Generator Terminal Box

For the parallel connection of 4 solar modules/ simulators each via one diode onto one output. Overvoltage protection Without function. Max. current per input 24 V/3 A DC-disconnector.



ST 06 S Inverter Island Grid

Transforms direct current into sinusoidal alternating current for operation of an island grid system. Input 12 V DC/8 A AC power approx. 100 W Available versions: 230 V / 50 Hz 230 V / 60 Hz 115 V / 60 Hz



ST 04 Solar Charge Controller

For monitoring of the state of charge state of the battery. Controls the loading process and the connection and disconnection of loads (low voltage disconnection). Operation status on LCD dispay.

Rated voltage 12 V/max 8 A



ST 07 AC Load Connection

For connection to the mains (via "ST 13 Mains connection) or to an inverter island grid ("ST 06 / ST 06 A") and operation of alternating current loads of max. 450 W Available versions: 230 V / 50-60 Hz 115 V / 60 Hz







ST 08 DC Load Connection

For connection to "ST 04 solar charge controller" and operation of direct current loads 12 V / max. 8 A



ST 12 Automatic Insulation Unit

For monitoring single-phase power feeding systems. It prevents uncontrolled island effects following failure or shutdown of the public electricity supply. Operating voltage 230 V / 50 Hz



ST 09 Battery Connection

For the connection of "ST 21 solar-battery" to "ST 04 charge controller"



ST 13 Mains Connection

Three-phase AC connection for connection of the public grid via a 5-pole CEE coupling 16 A to the training system. Adapter cable for single-phase available.



ST 10 Electric Meter

Single-phase electronic AC meter for measuring of the generated solar energy. Display of current power, kWh, measurement duration, inputting of tariff possible. Available versions: 230 V / 50 Hz 230 V / 60 Hz



ST 14 Module Stand

For the illumination of a 10 W solar module by means of a 400 W dimmable halogen spotlight. The inclination of the solar module and the height and distance of the spotlight to the solar module are Adjustable. The inclination of the spotlight can also be altered by fine adjustment. The solar module can be swung to simulate the sun's path during the day. Power supply 230 V / 50-60 Hz.



ST 11 Input /Supply Meter

Single-phase electronic AC meters for measuring of the solar energy fed into the grid and for measuring of the energy drawn from the grid. Display same as ST 10 Available versions: 230 V / 50 Hz 230 V / 60 Hz 115 V / 60 Hz







ST 15 Solar Module Connection Outdoor

For connection of the module "ST 22 Solar Module Outdoor" or similar to the socket on the front. The solar module is connecte to the two front sockets of the schematically shown solar module.



ST 19 Set of Safety Test Leads with movable laboratory stand

Highly flexible safety-test leads with 4 mm plugs. Contacts gold-plated brass/hard copper, inclusive movable laboratory stand with 2 brackets supplied with total 42 holding fingers. Lockable wheels, height 1.45 m



ST 16 Diode Series Connection

To perform the basic experiments "Characteristic curve of a diode" and "Characteristic curve of a diode series connection". Power supply external 24 V DC by "ST 27 Power Supply".



ST 20 AC AC Load

Panel 1 60 W bulb Standard plug socket with switch. Available versions: 230 V / 50-60 Hz 115 V / 60 Hz



ST 17 Shunt

For measuring current up to 1.5 A as voltage drop at the shunt resistance. E.g. for measurements in grid parallel operation circuits using an oscilloscope.



ST 20 AC AC Load

Panel 2 60 W bulb. Standard plug socket with switch. Available versions: 230 V / 50-60 Hz 115 V / 60 Hz



ST 18 Set of Safety Test Leads

Highly flexible safety-test leads with 4 mm plugs. Contacts gold-plated brass/hard copper, inclusive wall bracket with 21 holding fingers.



ST 20 AC AC Load

Panel 3 9 W Energy-saving lamp. Standard plug socket with switch. Available versions: 230 V / 50-60 Hz 115 V / 60 Hz (15 W)







ST 20 DC DC Load Panel 4

50 W halogen lamp, with switch, 12 V.



ST 23 DC Meter

Electronic DC meter for measuring direct current loads. Using in load cricuits. Display of current power and Wh, reset button.



ST 20 RW Set of electrical loads

Four variable resistors: 15 Ohm / 5,5 A 170 Ohm / 1,7 A 325 Ohm / 1,2 A 15,8 K.Ohm / 0.17 A



ST 24 Set Multimeter

Particularly robust. Automatic range selection, large display. DC / AC max. 1000 V, max. 10 A



ST 21 Solar Battery

Closed lead-gel battery especially for storing solar energy. Connected via "ST 09 battery connection" to "ST 04 solar charge controller" for operation of an island grid with storage. 12 V / 27 Ah C100.



ST 27 Power Supply

For the power supply of "ST 16 diode series connection" Control range 0 - 30 V DC/ 0-2 A Power supply: 115-230 V / 50-60 Hz.



ST 22 Solar Module Outdoor

Solar module for outdoor experiments. Angle of inclination adjustable, can be read off on a large degree scale Power 55 Wp Operation with "ST 15 Solar module connection outdoor".





ST 28 Solar Module polycrystalline ST 28 Solar Module amorphous Alternatively addidional solar module for "ST 14 module Frame". Quick change holder. Power: Polycrystalline ca. 10 W Amorphous ca. 5 W

ST 30 Fuse Box

Fuse box with 4-pole Flcircuit breaker, CEE plug and 1.5 m feed cable with CEE plug. 400 V / 50 Hz.

SOLARTRAINER





IKS Photovoltaik GmbH An der Kurhessenhalle 16 b 34134 Kassel / Germany Tel. +49 561 / 9538050 Fax + 49 561 / 9538051 Www.iks-photovoltaik.de info@iks-photovoltaik.de



Training systems Measurement engineering Special developments





Some user report on practical experiences:

Technikerschule Butzbach

"Solartrainer Profi has been in use for 15 years completely error-free and without repairs"



Handwerkskammer Münster

Already the prototype won over -Solartrainer Profi in successful operation since 1997"



Landesstelle Hessen für gewerbliche Berufsförderung in Entwicklungsländern

"Solartrainer Prof for multiplier training"



Bildungsinstitut Pscherer

"Fit for the job: basic and continuing vocational training with the Solartrainer Profi"



BZ Bildungszentrum Kassel

"Since 1997 more than 500 participants were trained with the Solartrainer Profi"



University of Nairobi

Institute of Nuclear Science and Technology

